

# Intellian t80Q

## Optimized for European Market

85cm Stabilized Ku-band Marine Satellite TV Antenna



### Optimized for European Market

Intellian provides just right solution for European customer's purpose. It's simple, easy, reliable and affordable. For vessels that may require global TV coverage in the future, a conversion kit is also available for WorldView LNB Model.

### DVB / DVB-S2 Signal Reception

The fully stabilized, 3-axis t80Q is an 85cm satellite TV antenna system that is exclusively designed to support viewing all Standard Definition (SD) and HD programming broadcast through both DVB and the latest DVB-S2 satellite TV service standards.

### Dedicated Management Ethernet Port

The Management Ethernet Port on the front of ACU enables direct and simple network connection between a PC and the ACU. The Management Port supports DHCP network connection by default, allowing automatic IP configurations and quick access to Intellian's remote management solution, Aptus Web.

### Global Satellite Library

The t80Q includes the pre-programmed global satellite library which allows boaters to select the desired satellite while travelling from region to region. Moving from one region to another is as simple as a few button taps on your Smart phone or Tablet.

### Rugged Construction

Built with Intellian's extremely high vibration and shock standards, the t80Q's simplified yet sophisticated mechanical design is capable of withstanding the most severe marine environment and is guaranteed to track and lock onto the satellite signal instantly in all weather conditions.

### Wireless Connectivity

The built-in Wi-Fi enables the ACU to be wirelessly connected and can be either turned on and off by a switch. Any kind of wireless devices such as PCs, laptops and smartphones can be used to connect to the ACU and monitor, control and change the settings of the system wirelessly.

# Intellian

Connect with the best


# Intellian t80Q

Optimized for European Market  
85cm Stabilized Ku-band Marine Satellite TV Antenna


## Technical Specifications

Physical		
Radome Height	120.5cm / 47.4"	
Radome Diameter	113cm / 44.5"	
Reflector Diameter	85cm / 33.5"	
Weight	82.2Kg / 181.2lbs	
Environmental		
Operating Temp. Range	-25°C to +55°C / -13°F to +131°F	
Storage Temp. Range	-40°C to +80°C / -40°F to +176°F	
Water Ingress	IPX6	
Approvals	CE / FCC	
Warranty	3 year parts and 2 year labor	
Performance		
Reception Frequency	Ku-band (10.7~12.75GHz)	
Polarization	Vertical / Horizontal	
Minimum EIRP	44dBW	
Azimuth Range	680°	
Elevation Range	-15° to +110°	
Ship's Motion	Roll ±25°, Pitch ±15°, Yaw ±8° @ 6 sec period	
Turning Rate	Up to 12°/sec & 5°/sec <sup>2</sup>	
RF Output	Quad Output	
Antenna Control Unit		
Dimensions (WxDxH)	43.1cm x 38cm x 4.4cm / 17" x 15" x 1.7"	
Weight	3.5kg / 7.7lbs	
Display	2 line 40 Character VFD module	
GPS Interface	Built-in (NMEA 0183 GPS)	
Power Requirement	100~240V AC, 50~60Hz, 2A	
Power Consumption	Typ.50W, Max. 100W	
LNB LO Frequencies		
Local Oscillator Frequency	<b>Polarization</b>	<b>Area</b>
Universal Low: 9.75 GHz High: 10.6 GHz	Quad Linear	Europe, Middle East, Africa, some Asia countries
<b>Note</b>	<ul style="list-style-type: none"> <li>LNB stability : +/- 1.0MHz (25°C)</li> <li>Low / High band Switching Low Band : 0KHz , High Band 22KHz±4KHz</li> </ul>	

## System Diagram



## Coverage Map



# Intellian

**Global HQ**  
Innovation Center / Factory  
Intellian Technologies, Inc  
T +82 31 379 1000  
F +82 31 377 6185

**APAC**  
Seoul Office  
Intellian Technologies, Inc.  
T +82 2 511 2244  
F +82 2 511 2235

**Americas**  
Irvine Office  
Intellian Technologies USA, Inc.  
T +1 949 727 4498  
F +1 949 271 4183  
Toll Free +1 888-201-9223

**EMEA**  
Rotterdam Office  
Intellian B.V.  
T +31 1 0820 8655  
F +31 1 0820 8656